

# LADN02

## TeSys D - auxiliary contact block - 2 NC - screw-clamps terminals



### Main

|                              |  |
|------------------------------|--|
| Commercial Status            | Commercialised   |
| Range                        | TeSys  |
| Product or component type    | Auxiliary contact block  |
| Product compatibility        | CR1F   |
| Auxiliary contacts operation | Instantaneous  |
| Pole contact composition     | 2 NC   |
| Connections - terminals      | Screw clamp terminals 2 cable 1...2.5 mm <sup>2</sup> - cable stiffness: solid - without cable end<br>Screw clamp terminals 2 cable 1...2.5 mm <sup>2</sup> - cable stiffness: solid - with cable end<br>Screw clamp terminals 1 cable 1...2.5 mm <sup>2</sup> - cable stiffness: solid - without cable end<br>Screw clamp terminals 1 cable 1...2.5 mm <sup>2</sup> - cable stiffness: solid - with cable end<br>Screw clamp terminals 2 cable 1...2.5 mm <sup>2</sup> - cable stiffness: flexible - without cable end<br>Screw clamp terminals 2 cable 1...2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end<br>Screw clamp terminals 1 cable 1...2.5 mm <sup>2</sup> - cable stiffness: flexible - without cable end<br>Screw clamp terminals 1 cable 1...2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end |

### Complementary

|   |   |
|---|---|
| Mounting location                           | Front   |
| [Ui] rated insulation voltage               | 600 V - certifications CSA<br>690 V - conforming to IEC 60947-5-1<br>600 V - certifications UL                                    |
| [Ue] rated operational voltage              | 690 V AC 25...400 Hz  |
| [Ith] conventional free air thermal current | 10 A at ≤ 60 °C   |
| Irms rated making capacity                  | 250 A at ≤ 690 V DC conforming to IEC 60947-5-1<br>140 A at ≤ 690 V AC conforming to IEC 60947-5-1                                |
| Permissible short-time rating               | 140 A at -5...60 °C 100 ms<br>120 A at -5...60 °C 500 ms<br>100 A at -5...60 °C 1 s   |
| Protection type                             | GG fuse ≤ 10 A rating according to operational current for Ue ≤ 690 V   |
| Associated fuse rating                      | 10 A gG IEC 60947-5-1   |
| Mechanical durability                       | 30 Mcycles  |
| Minimum switching current                   | 5 mA  |
| Minimum switching voltage                   | 17 V  |
| Non-overlap time                            | 1.5 ms on energisation (no overlap between NC and NO contact)<br>1.5 ms on de-energisation (no overlap between NC and NO contact) |
| Overlap time                                | 1.5 ms  |
| Insulation resistance                       | > 10 MOhm   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|                                       |   |
|---------------------------------------|---|
| Environmental characteristic          | Normal environment  |
| Standards                             | BS 4794<br>EN 60947-5-1<br>IEC 60947-5-1<br>NF C 63-140<br>VDE 0660 |
| Product certifications                | CSA<br>UL   |
| IP degree of protection               | IP2x conforming to VDE 0106   |
| Protective treatment                  | TH conforming to IEC 60068  |
| Ambient air temperature for operation | -5...60 °C  |
| Ambient air temperature for storage   | -60...80 °C   |
| Operating altitude                    | 3000 m without derating in temperature                              |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS                             | Compliant - since 0629 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                              |
| Product end of life instructions | Need no specific recycling operations   |